



American National Rubber

PO Box 878 ** Ceredo, West Virginia 25507 ** Telephone: 1-800-624-3410 ** Fax: 304-453-2347

DATA SHEET

NEOPRENE

4119-N

Color:		Black
Specifications:	ASTM D-1056-00	2C1
	ASTM D-1056-67 ⁽¹⁾	SCE41
	SAE J18-02	2C1
	GM 6086M ⁽³⁾	II
	GMN11106 ⁽³⁾	II
25% Compression Deflection (PSI)		2 - 5
Shore 00 Durometer (Approximate)		30 - 50
Density (Approximate p.c.f.)		7 - 13
Water Absorption By Weight		5%
Temperature Range		-70 to 200F
Weather Resistance:	UV	Excellent
	Ozone	Fair
Accelerated Linear Shrinkage (Typical)		5%
Fuel B Resistance %		250
Tensile Strength (Typical)		60 PSI
Elongation (Typical)		150%
Flammability:	FM VSS No. 302	Pass
	ASTM D 6576	Pass
	UL 94 HBF	Pass (UL Listed)
	UL 94 HF1	Pass (UL Listed)

(1)Obsolete specification listed for reference only. ANR certifies to most recent revision of ASTM D-1056 and SAE J18.

(3)Certain sections of this specification will not apply to all products. Contact Customer Service for details.

American National Rubber disclaims responsibility for results of use of this information, which is furnished without charge, or of any product mentioned herein. It is the user's responsibility to make and be guided by his own testing before making a final decision on the type of material to be used in any application.

ISO 9001-2000 Certified Company

06/06