

Commercial Grade EPDM Sheet

Commercial Grade EPDM Sheet

Commercial blend EPDM is the most economical EPDM sheet offered. Intended to be used in less critical applications where temperatures are of an intermittent nature.

Finish: Smooth

Durometer Hardness Shore \pm 5	Thickness (Inches)	Width (Inches)	Tensile* PSI	Ultimate Elongation* Percent	Temperature Range	Estimated Weight Per Linear Foot (1/8" x 36")	Specifications
40	1/16 - 1/4	36, 48	800	300	-40°F to +212°F	2.4 lb	ASTM D 2000 SAE J200 3BA 408 C12 MIL R-3065 RS 408 C12
50	1/16 - 1/4	36, 48	800	300	-40°F to +212°F	2.5 lb	ASTM D 2000 SAE J200 3BA 508 C12 MIL R-3065 RS 508 C12
60	1/16 - 1/4	36, 48	800	250	-40°F to +212°F	2.6 lb	ASTM D 2000 SAE J200 3BA 608 C12 MIL R-3065 RS 608 C12
70	1/16 - 1/4	36, 48	800	150	-40°F to +212°F	2.7 lb	ASTM D 2000 SAE J200 3BA 708 C12 MIL R-3065 RS 708 C12

*Physicals presented are typical values