

VINYL FOAM SERIES

RP1100, RP1200, RP1300



Vinyl Foam RP1100-RP1200 Series is formulated especially for use in gasketing and sealing. The closed cell structure resists absorption of water and other fluids, provides good load bearing qualities and helps maintain a permanent positive seal when employed as a gasketing material.

Tape No. & Color	RP1112 GRAY RP1212 BLACK	RP1118 GRAY RP1218 BLACK	RP1125 GRAY RP1225 BLACK	RP1312 GRAY	RP1318 GRAY	RP1325 GRAY	RP1337 GRAY
Thickness<	1/8"	3/16"	1/4"	1/8"	3/16"	1/4"	3/8"
Density	10-13 lbs./ft ³	10-13 lbs./ft ³	10-13 lbs./ft ³	5.5-10 lbs./ft ³	5.5-10 lbs./ft ³ <	5.5-10 Lbs./Ft ³	5.5-10 lbs./ft ³ <
Hardness (Shore OO) Average	25-45 lb.	25-45 lb.	25-45 lb.	30-40 lb.	30-40 lb.	30-40 lb.	30-40 lb.
Compression Deflection 25% (psi)	3.0-2.5 lb.	3.0-2.5 lb.	3.0-2.5 lb.	.5-2.5 lb.	.5-2.5 lb.	.5- 2.5 lb.	.5-2.5 lb.
Roll Length, Feet	75 ft.	45 ft.	45 ft.	75 ft.	45 ft.	45 ft.	30 ft.

Other widths, die cut and kiss cut parts will be quoted upon request.

The above product information and specifications are based upon research and believed to be true but do not constitute a warranty. All products are sold with the understanding that the purchasers will determine the suitability of the materials for their purpose. HST Materials will supply samples for your testing and product evaluation.